

MARK

PRIMACOL ® PROFESSIONAL

PRODUCT

Concrete & flooring**Paint for concrete floors**

- Durable, weather-resistant coating
- Resistant to scrubbing
- Resistant to detergents
- Perfect coverage
- Increased resistance to mechanical damage



CAPACITY

0.75l 2.2l 4.5l

PROPERTIES

Designed for decorative and protective painting of floors and other concrete surfaces. Suitable for indoor use (garages, basements, workshops, warehouses, boiler rooms) and for outdoor painting of concrete elements such as terraces, fences, balconies, facades, garages, garden architecture, walls, and sidewalks. The product can also be used for painting lanes and markings on parking lots, roads, and sidewalks.

The paint creates a coating with good adhesion to concrete substrates. It is characterized by high resistance to scrubbing (at least 10,000 cycles) (PN-92/C-81517 standard), as well as to oils, gasoline, and detergents. The paint is not recommended for typical industrial applications with very heavy loads and traffic.

HOW TO USE

The temperature of the air and surfaces to be painted must not be lower than +5°C and not higher than +25°C. Work should not be carried out in rain, fog, or on very hot days. Use water and detergent to clean painting tools. Before putting the premises into use, air them out until the odor disappears.

SUBSTRATE
PREPARATION

Before painting, the surface should be properly prepared: dry, dust-free, and free from grease and dirt. Loose elements and old coatings should be removed from the surface. Remnants of old coatings can reduce the paint's bond strength. For surfaces affected by mold, remove the mold using Primacol. Antifungal 2.

Stir the paint thoroughly before use. When applying to new concrete floors, a primer is recommended. To do this, dilute the paint with water in a 3:1 ratio (3 liters of paint + 1 liter of water). This increases the paint's penetration into the substrate and therefore improves its adhesion. Apply subsequent coats undiluted.

STORAGE

The paint should be stored at a temperature of 5–25 °C, in tightly closed, original packaging, in a dry place, away from direct sunlight.

Keep this product out of the reach of children. Detailed information can be found in the product safety data sheet.

SECURITY

Product treated with a biocidal product. Contains C(M)IT/MIT (3:1). Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 1,2-benzisothiazol-3 (2H)-one. May cause an allergic reaction.

Caution! Spraying may produce hazardous respirable droplets. Do not inhale spray or mist.

TECHNICAL DATA

Chemical composition	A suspension of mineral fillers, pigments, polymer dispersion and additives	Touch drying time	4 hours
Smell	Light, gentle	Total drying time	48 hours
pH	7.5-8.5	Efficiency	8-12 m ² / l
Density	1.35 g/ cm ³	Washing tools	Water with detergent
Appearance of the dry film	Semi-matt	Thinner	Water
Number of layers	2	VOC content	max.25g/l (cat. A/c/FW) 40g/l
Second layer after	3 hours	Application method	Brush, roller

LEGAL INFORMATION

All information and data contained in this data sheet are provided in good faith and to the best of our laboratory's knowledge. However, they must be considered as indications without warranty if the product is beyond our control. This technical information does not constitute a certificate of product quality or an offer. The manufacturer is not responsible for any misuse of the information contained in this data sheet or for any consequences resulting therefrom. If in doubt, always conduct a test. The manufacturer reserves the right to change the above data without notice.